

Light Duty Commercial Wall Hung Energy Saver Electric Water Heater



Photo is of
LD-WH6U3-1

The Light Duty Wall Hung Electric Models Feature:

- **Fully Automatic Controls**—Fast acting surface-mount thermostat for automatic temperature control. Factory installed sensitive manual reset energy cut-off for safety to prevent overheating.
- **Direct Heat Transfer With a Single Immersed Element**—Transfers heat directly and efficiently to the water. Screw-in style element.
- **Vitraglas® Lining**—Bradford White tanks are lined with an exclusively engineered enamel formula that provides superior tank protection from the highly corrosive effects of hot water. This formula (Vitraglas®) is fused to the steel surface by firing at a temperature of over 1600°F (871°C).
- **1" Non-CFC Foam Insulation**—Covers the sides and top of tank, reducing the amount of heat loss. This results in less energy consumption, improved operation efficiencies and jacket rigidity (30 gallon model has 2").
- **Factory Installed Heavy Duty Wall Mounting Bracket**—no additional brackets or modifications required.
- **Water Connections**—3/4" NPT factory installed true dielectric fittings extend water heater life and eases installation. Located on the bottom for easier installation.
- **Protective Magnesium Anode Rod**—Provides added protection against corrosion for long trouble-free service.
- **Steel Tank**—Heavy gauge steel automatically formed, rolled, and welded.
- **Voltages Available**—120V, 208V, 240V, 277V, 480V.
- **Single Phase Operation Only.**
- **T&P Relief Valve**—Included.



Copper Screw Type Immersion Element
(Incoloy type immersion element available upon request)



3 or 5-Year Limited Tank Warranties / 1-Year Limited Warranty on Component Parts.

For more information on warranty, please visit www.bradfordwhite.com

For products installed in USA, Canada and Puerto Rico. Some states do not allow limitations on warranties. See complete copy of the warranty included with the heater.

MANUFACTURED UNDER ONE OR MORE OF THE FOLLOWING U.S. PATENTS: 5,682,666; 7,634,976; 5,660,165; 5,954,492; 6,056,542; 6,935,280; 5,372,185; 5,485,879; 5,574,822; 7,971,560; 7,992,526; 6,684,821; 6,442,178; 7,334,419; 7,866,168; 7,270,087; 7,007,748; 5,596,952; 6,142,216; 7,699,026; 5,341,770; 7,337,517; 7,665,211; 7,665,210; 7,063,132; 7,063,133; 7,559,293; 7,900,589; 5,943,984; 8,082,888; 5,988,117; 7,621,238; 7,650,859; 5,761,379; 7,409,925; 5,277,171; 8,146,772; 7,458,341; 2,262,174. OTHER U.S. AND FOREIGN PATENT APPLICATIONS PENDING. CURRENT CANADIAN PATENTS: 2,314,845; 2,504,824; 2,108,186; 2,143,031; 2,409,271; 2,548,958; 2,112,515; 2,476,685; 2,239,007; 2,092,105; 2,107,012. Vitraglas® is a registered trademark of Bradford White® Corporation.

Commercial Electric Water Heater

Light Duty Wall Hung Energy Saver Models

Meet or exceed ASHRAE 90.1b (current standard) C.E.C. Listed

Model Number	Capacity		First Hour Rating** Gal.	Recovery 100°F Rise		A Height	B Jacket Dia.	C Wall to Front	D Height to Bracket	E Height to T&P Conn.	F Top of Heater to Electrical Access in.	Approx. Shipping Weight
	U.S. Gal.	Imp. Gal.		U.S.* GPH	Imp.* GPH	in.	in.	in.	in.	in.	in.	lbs.
LD-WH6U3-1†	6	5	—	6	5	15¾	14	14⅝	11¾	11⅞	17	33
LD-WH12U3-1	12	10	—	6	5	16⅜	18	18⅝	12¾	12½	19⅞	48
LD-WH20L3-1	19	16	—	6	5	24⅜	18	18⅝	18¼	21	19⅞	59
LD-WH30L3-1	30	25	19	6	5	29¼	22	22⅝	23	25¾	23⅞	82

Model Number	Capacity		First Hour Rating** Liters	Recovery 56°C Rise		A Height	B Jacket Dia.	C Wall to Front	D Height to Bracket	E Height to T&P Conn.	F Top of Heater to Electrical Access mm.	Approx. Shipping Weight
	Liters			Liters/* Hour	mm.	mm.	mm.	mm.	mm.	mm.	mm.	kg.
LD-WH6U3-1†	23	—	—	23	—	400	356	372	298	302	432	15
LD-WH12U3-1	45	—	—	23	—	416	457	473	314	317	505	22
LD-WH20L3-1	72	—	—	23	—	619	457	473	464	533	505	27
LD-WH30L3-1	114	—	72	23	—	743	557	575	584	654	606	37

Specify wattage and voltage when ordering. Use chart to right for maximum wattages at certain voltages.

†Maximum wattage at any voltage is 3000W.


For 5 year models, change suffix "3" to "5".

Single element only.

*Based on 1500W operation.

**First Hour Rating is based on the latest AHRI Directory listings.

NSF Construction not available.



Wattage	Recovery GPH Temperature Rise °F				
	60	80	90	100	120
1500W	10	8	7	6	5
2000W	14	10	9	8	7
2500W	17	13	11	10	9
3000W	21	15	14	12	10
3500W	24	18	16	14	12
4000W	28	21	18	16	14
4500W	31	23	21	19	15
5000W	34	26	23	21	17
5500W	38	29	25	23	19
6000W	41	31	28	25	21

Wattage Limitations	Voltage				
	120V	208V	240V	277V	480V
1500W	yes	yes	yes	yes	yes
2000W	yes	yes	yes	yes	yes
2500W	yes	yes	yes	yes	yes
3000W	yes	yes	yes	yes	yes
3500W	no	yes	yes	no	no
4000W	no	yes	yes	yes	yes
4500W	no	yes	yes	yes	yes
5000W	no	yes	yes	yes	yes
5500W	no	yes	yes	no	no
6000W	no	yes	yes	yes	yes

General

All models ETL listed. These heaters are wired Single Phase, 120V with one 1500W element, unless otherwise specified.

All water and electrical connections are 3/4" (19mm)NPT.

All models certified at 300 psi test pressure (2068 kPa) and 150 psi working pressure (1034 kPa).

Applicable models CSA verified for energy performance in accordance with C191.1-M90.

Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.



For U.S. and Canada field service, contact your professional installer or local Bradford White sales representative.

Sales 800-523-2931 • Fax 215-641-1670 / Technical Support 800-334-3393 • Fax 269-795-1089 • Warranty 800-531-2111 • Fax 269-795-1089

International: Telephone 215-641-9400 • Telefax 215-641-9750 / www.bradfordwhite.com

BRADFORD WHITE-CANADA INC. Sales / Technical Support 866-690-0961 / 905-238-0100 • Fax 905-238-0105 / www.bradfordwhite.com

Built to be the Best™

©2013, Bradford White Corporation. All rights reserved.