


Brute® LX



Wall Mounted, Residential Combination Boiler

Indoors, Models BLXC 125, 150, 175



Submittal Data

Date:

Project #:

Engineer:

Prepared By:

Bid Date:

Project Name:

Location:

Contractor:

Standard Equipment

- High condensing efficiency
- Modulation down to 20% of full fire (5:1 turndown)
- Sealed combustion chamber
- Pre-mix stainless steel burner
- Low NOx system exceeds the most stringent regulations for air quality – 10ppm NOx
- Horizontal or vertical direct vent
- Vent and air pipe lengths of up to 150 equivalent feet (each)
- Horizontal vent and air terminals
- Stainless steel heat exchanger with welded construction
- ASME 30 psi (207kPa) working pressure heat exchanger
- ASME "H" stamp
- 30 psi (207kPa) ASME pressure relief valve
- Auto cascade setup
- Stainless Steel brazed-plate DHW heat exchanger with priority for on-demand hot water
- Boiler pump wired and mounted inside jacket
- Built-in condensate trap and drain, priming not required
- Automatic air vent
- Temperature and pressure gauge
- Boiler water pressure switch
- Blocked vent pressure switch
- Blocked condensate pressure switch
- Burner site glass
- Electronic PID modulating control
- Direct spark ignition
- Multiple pump control for boiler pump and system pump, each with delay
- Customizable Freeze Protection
- Anti-short cycling
- Large user-interface and display
- Alarm output
- Accepts external (4-20mA or 0-10VDC) modulation signal
- Outdoor reset (sensor included)
- Outdoor air reset curve
- Vent temp auto turn-down before lockout
- Manual reset high limit
- Lighted on/off toggle switch
- Wall mount bracket
- Field convertible between natural gas and propane
- Zero clearance to combustible surfaces
- 15-Year limited warranty
- 2-Year parts warranty

Boiler Data

Number of Units:

Fuel

- ☐ Natural
☐ Propane

Options

- ☐ Low Water Cut-off



Accessories for Field Mounting

☐ Horizontal concentric vent kit	☐ Concentric elbow, 90°	☐ Concentric flush-mount 2" terminal
☐ Concentric vent adapter	☐ Wall plate for concentric pipe	☐ Concentric flush-mount 3" terminal
☐ Concentric pipe, 12" long	☐ Horizontal concentric sstl terminal	☐ Condensate Neutralizer
☐ Concentric pipe, 24" long	☐ Horizontal concentric 2" PVC terminal	
☐ Concentric pipe, 36" long	☐ Horizontal concentric 3" PVC terminal	
☐ Concentric pipe, 13"-18" telescoping		

Sizing Data

Model	Input		Output		DHW Output @ 75°F Rise	AFUE	Gas Conn. Size inches	Water Conn. Size inches	DHW Conn. Size inches	Shipping Weight	
	BTU/h	kW	BTU/h	kW						lbs	kg
☐ BLXC 125	125,000	36.6	118,750	34.8	3.1 gpm	95%	1/2" NPT	3/4" NPT	1/2" NPT	133	60
☐ BLXC 150	150,000	43.9	142,500	41.8	3.7 gpm	95%	1/2" NPT	1" NPT	1/2" NPT	148	67
☐ BLXC 175	175,000	51.6	166,250	48.7	4.3 gpm	95%	1/2" NPT	1" NPT	1/2" NPT	163	74

NOTES:

- For other boiler ratings:

$$\text{Boiler Horsepower: HP} = \frac{\text{Output}}{33,475} \quad \text{Radiation Surface: EDR sq. ft.} = \frac{\text{Output}}{150}$$

Electrical Data

Size	Boiler		
	Volts	Phase	Amps
BLXC 125	120	Single	1.5
BLXC 150	120	Single	1.5
BLXC 175	120	Single	2.2

* Minimum 15A circuit required

Vent System

INTAKE / EXHAUST Max Equivalent Vent and Air Pipe Length (each)									
SIZES	STANDARD 2-PIPE			STANDARD 2-PIPE			OPTIONAL CONCENTRIC		
	DIA.	FT.	m	DIA.	FT.	m	DIA.	FT.	m
125 - 175	2"	40	12.2	3"*	150	45.7	3/5"	40	12.2

* Must use 2x3 adapter within 1 ft. (30cm) of boiler.

Reference the Installation and Operation Manual for more details.

Dimensional Data


Model	Dimension							
	A	B	C	D	E	F	G	H
125 MBH	1" (3)	15-1/2" (39)	1-1/4" (3)	12-3/4" (33)	11" (28)	1-1/4" (3)	9-1/2" (24)	14-3/4" (37)
150, 175 MBH	1-1/2" (4)	15-1/4" (39)	1-3/4" (4)	13" (33)	11-1/4" (28)	2-3/4" (7)	5-1/4" (14)	2" (5)

inches (cm)

Model	J*	K	L	M	N	O
125 MBH	2-3/4" (7)	12-3/4" (33)	2" (5)	30-1/2" (78)	18" (46)	4-5/8" (12)
150, 175 MBH	2-3/4" (7)	12-3/4" (33)	1-3/4" (5)	35-1/2" (90)	18" (46)	8-7/8" (23)

inches (cm)

* - J dimension applies for both the DHW OUTLET and DHW INLET



Domestic Hot Water Heating Capacity

Model	35°F Rise		45°F Rise		77°F Rise		DHW Connection Size
	GPM	l/m	GPM	l/m	GPM	l/m	in.
MLXCW125	6.8	24.6	5.3	20.1	3.1	11.7	1/2"
MLXCW150	8.1	30.1	6.3	23.8	3.7	14.0	1/2"
MLXCW175	9.5	36.0	7.4	28.0	4.3	16.3	1/2"

Clearances

APPLIANCE SURFACE	SUGGESTED SERVICE ACCESS CLEARANCE	
	INCHES	CM
Left Side	6	15
Right Side	6	15
Top	12	30
Closet, Front	6	15
Front	24	61
Bottom	24	61
Vent	1	3

Certified by CSA for zero clearance to combustible materials on all sides.

Bradford White reserves the right to change specifications, components, features, or to discontinue products without notice.



200 Lafayette St.
Middleville, MI 49333
Warranty: (800) 531-2111

www.BradfordWhite.com

Litho in U.S.A. © Bradford White 1712 Document 1298D-BW